



Description

- Everlastic® EJ-2000 is a cross linked closed cell foam.
- Gray in color.

Applications

- Expansion joint filler with hot or cold applied sealants, pipe and thermal wrap, acoustica partition closures, corrugated deck closures, column isolation wrap, and other uses.

Available Sizes

- Standard thickness 3/8" and 1/2". Other sizes skived or laminated.
- Standard rolls are 60" x 50'-0".
- Available multi score, standard score and tear tab to allow sealant reservoir.
- Available with self-stick, pressure sensitive adhesive (PSA) on one or two sides.
- Die cut parts Available.

Typical Physical Properties

Typical Physical Properties		Test Method	Typical Results
Density:	lb/ft ³	ASTM D- 3575	2
Tear resistance	pi	ASTM D- 3575	10
Compression Deflection	10% defection	ASTM D- 3575	2.6 psi
	25% defection		5.6 psi
	40% defection		9.2 psi
	50% defection		13.5 psi
Compression Set	(22 hrs @50%)	ASTM D- 3575	23%
Elongation	%	ASTM D- 3575	135
Tensile Strength	psi	ASTM D- 3575	37
Water Absorption	(lb/sf of cut surface) %	ASTM D-1056	< 0.07
K Factor		ASTM C -177	0.25



To the best of our knowledge this published information is accurate, however, to determine suitability of material/product for a specific application is the user's responsibility. Williams Products, Inc. shall not be liable for any loss or damage resulting from inappropriate usage.

WILLIAMS PRODUCTS, INC.

1750 MAPLELAWN BOULEVARD - TROY MICHIGAN 48084 - PHONE (248) 643-6400 - TOLL FREE (800) 521-9594 - FAX (248) 643-7117

www.williamsproducts.net